



# PRODUCT COPY: AIRWORX 55T FACELIFT

## AIRWORX- 55T

**BIGGER RESULTS FROM A SMALLER MACHINE!**

**A FRESH LOOK FOR THE AIRWORX 55T**

Compacting its size hasn't meant shortchanging its performance.

With a range of new features, the AIRWORX 55T upgrades productivity and efficiency.

### WHAT'S NEW?

- Load Easier and transport upright with the new shorter filter silo.
- Dial up suction capacity with 15% additional primary filter surface area.
- Operate easily with improved ergonomics
- Increase project productivity and efficiency
- Improve maneuverability where it's tight

### KEY UPDATED FEATURES: *(see diagram on next page)*

- 260mm lower in height... makes van/trailer transport easy
- New filter sock set up – 19 socks that really suck
- 100mm shorter frame – no more oversized pallet loads and improved performance in tight spaces
- Repositioned accessory machine outlet – easier access
- Updated labelled control panel
- Broom and wand transport handles
- Easy access bag changing





260mm lower in height

Broom and wand transport handles

100mm shorter frame  
no more oversized pallet loads  
& improved performance in tight spaces

Updated labelled control panel



Easy van/trailer storage and transportation!



Repositioned accessory machine outlet for easier access



New filter sock set-up  
19 socks that really suck!





## Applications:

- Elimination of hazardous airborne dust in the grinding/sanding of concrete/masonry/timber applications.
- Industrial applications where high suction is required.

## Features:

- Frequency controlled vacuum pump offering the following benefits:
  - i. 40% more airflow than standard machines on regular power supply.*
  - ii. Variable suction control (can be used for hand grinders through to large floor grinding machines).*
  - iii. Generator friendly soft start.*
  - iv. Sophisticated electronic motor protection.*
  - v. Automatic direction correction.*
- Time saving radio controlled on/off (but also includes manual on/off).
- Reliable 2-stage filter sock & micro filter particle filtration.
- Large puncture proof wheels for easy transportation over rougher surfaces.
- Excellent ground clearance.
- Fits through standard doors.
- Rear "bull horns" for transportation of power leads & vacuum hoses.
- Easily folds forward to enable compact transportation.
- Unique bag-disposal system for containment of messy and hazardous substances (continuous bag compatible).
- Washable polyester filters (M-Class only).
- Power outlet for grinding machine.
- Highly mobile & flexible unit.
- All metal super-industrial strength construction.
- 3" (75mm) hose inlet.
- Quiet operation with integrated WORX+ silencer.
- H class option – 99.999% @ 1µm particle size.





TECHNICAL INFORMATION:

<b>Motor (3~Phase)</b>	5.5kW 380-480V
<b>Rated Current</b>	15A Max (6-12A normal use depending on speed setting)
<b>Weight</b>	260 kg
<b>Max Airflow (Approximately)</b>	650 m <sup>3</sup> / hr
<b>Maximum Vacuum</b>	300 mbar
<b>Suction inlet</b>	Ø75 mm
<b>Primary filtration surface area</b>	2.78m <sup>2</sup>
<b>Micro filter surface area</b>	6.5 m <sup>2</sup>
<b>Length x Width x Height (Upright)</b>	1200 x 760 x 1700mm
<b>Length x Width x Height (Folded)</b>	1870 x 760 x 1325mm

